

INDUSTRIAL VALVES





**BALL VALVE
1 PC SCREWED**

M.O.C: CF8,CF8M
MFG. STD: BS 5351 TESTING : BS 6755
DESIGN: 1PC
RATING: 150#
SIZE: 15 MM TO 100 MM
END: SCREWED/SOCKET WELD
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**BALL VALVE
3 PC SCREWED**

M.O.C: CF8, CF8M
MFG. STD: BS 5351 TESTING : BS 6755
DESIGN: 3PC
RATING: 150#
SIZE: 15 MM TO 50 MM
END: SCREWED/SOCKET WELD
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**BALL VALVE
3 PC FLANGED**

M.O.C: CF8,CF8M
MFG. STD: BS 5351 TESTING : BS 6755
DESIGN: 3PC
RATING: 150#, 300# & 600#
SIZE: 15 MM TO 150 MM
END: FLANGE END
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)



**BALL VALVE
2PC FLANGED**

M.O.C: C.S CF8,CF8M
MFG. STD: BS 5351 TESTING : BS 6755
DESIGN: 2PC
RATING: 150#, 300# & 600#
SIZE: 15 MM TO 150 MM
END: FLANGED
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**WCB 3PC FLANGED
BALL VALVE**

M.O.C: C.I, C.S,M.S
MFG. STD: BS 5351 TESTING : BS 6755
DESIGN: 3PC
RATING: 150#, 300# & 600#
SIZE: 15 MM TO 150 MM
END: FLANGE END
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)



**GLOBE
VALVE**

M.O.C: WCB, CF8,CF8M
MFG. STD: API 600
TESTING : API 598
RATING: 150#, 300#, & 600#
SIZE: 25 MM TO 300 MM
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**SWING
TYPE NRV**

M.O.C: CF8,CF8M
MFG. STD: BS1686
RATING: 150#, 300#, 600#
SIZE: 25 MM TO 300 MM
END: FLANGED
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**GATE
VALVE**

M.O.C: WCB, CF8,CF8M
MFG. STD: API 600 TESTING : API 598
RATING: 150#, 300# & 600#
SIZE: 25 MM TO 300 MM
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)
PNEUMATIC AIR TEST: 7KG/ CM2



**WAFER
TYPE NRV**

M.O.C: CF8,CF8M
MFG. STD: API 600 TESTING : API 598
RATING: 150#
SIZE: 25 MM TO 300 MM
BODY: 425 PSI (30 KG/ CM2)
SEAT: 300 PSI (21 KG/CM2)



**DISC CHECK
VALVE**

M.O.C: CF8,CF8M
MFG. STD: BS5155
RATING: PN 10, PN 16
SIZE: 50 MM TO 150 MM
BODY: 225 PSI (16 KG/ CM2)
SEAT: 165 PSI (11 KG/CM2)



**"Y" TYPE
STRAINER**

BODY/ COVER: CF8/CF8M
END: FLANGED/ SCREWED
SIZE: 15 MM TO 600 MM
RATING: 150#



**IC SIGHT
GLASS**

M.O.C: IC CF8/ CF8M
DESIGN: FULL VIEW TYPE
SIZE: 1/2"-6"
END: FLANGE ENDS ASA 150#



**WCB TUBE
GLASS**

M.O.C: MILD STEEL
DESIGN: FULL VIEW TYPE
SIZE: 1/2" - 6"
END: FLANGE ENG ASA 150#



**DOUBLE
WINDOW TYPE**

M.O.C: IC CF8/ CF8M
DESIGN: DOUBLE WINDOW
SIZE: 1"-4"
END: FLANGE ENDS ASA 150#



PREMOULD CORPORATION

Plot No. 535/E/1F, First Floor, Road No. 5, GIDC,
Sachin, Surat-394230.(Guj.) INDIA.

+91-9898 3054 66
+91-9173 9173 68

Email : premouldcorp@gmail.com